



A short and strong pulse erases the data on the hard disk irrevocably

- Simple operation
- Floods the media with a very strong magnetic field





TOP SECRET DATA PROTECTION AND AUDIT COMPLIANCE



When degaussing, the storage media are flooded with a very strong magnetic field that far exceeds their own magnetic force, the coercivity of the hard disk. The short and strong pulse erases the data on the hard disk irrevocably. Degaussing is characterized above all by the simple operation and minimal space requirements, which also allows for its use in an office environment.

intimus sets the Standard for audit compliance with its new Auditor-Pro erasure verification system. A specially designed image capture system records the erasure of each hard disk drive or tape processed by the intimus 20000 NSA/CSS EPL-Listed Degausser. Using the included barcode scanner, the user records the serial number of the hard Disk or tape and associates an image of the disk or tape at the time of erasure.





WHY INTIMUS 20000

- NSA (NSA/CSS EPL-912A-E) approved
- NATO listed
- Clean and quiet solution to sanitize magnetic media
- Single Pass Pulse Technology
- Drawer Feeding Solution
- Information Display
- Internal Verification of Magnetic Field
- Integrated Handles

OPTIONAL EQUIPMENT

- Transportcase, Shock-resistant plastic, on rollers, lockable
- Including pre-molded parts for a safe transporation of goods



Art. No. 93202

W/D/H 64 x 69 x 81 cm



BARCODE SCANNER Scans hard drive serial numbers as you degauss



STYLUS For use with the touch screen control head

AUDITOR-PRO FEATURES

- Creates a secure erasure verification process
- Automated image capture system that recoreds images of degaussed hard drives
- Scans serial numbers of degaussed hard drives
- Documents operator ID with up to two witnesses and erasure status of hard drives
- Generates Auditor-Pro erasure report with images for audit compliance
- Provides proof data is completely eliminated
- Touch screen control head
- Auditor-Pro erasure report software
- Barcode scanner and stand
- Stylus
- Auditor-Pro software support for one year
- 50 "Degaussed" labels for erased hard drives

WWW.INTIMUS.COM



SCREENSHOTS



Opening screen



Accept or reject image



Secure login



List view of erasure status

| | | | Wait | ting for d | ata fro | m degau | 1556r | | |
|---|---|----|--------|------------|---------|---------|-------|---|-----------|
| | | | SERIAL | NUMBER | 591 | озтр | 55689 | | 55 |
| | | IN | CIDENT | NUMBER | 351 | 4 | | | NEX |
| 1 | 2 | з | 4 | 5 | 6 | 7 | 8 | 9 | 0 |
| Q | w | E | R | т | Y | U | 1 | 0 | Р |
| | 5 | D | F | G | н | I. | к | L | <- |
| A | | | | | | | | | |

Data collection



Proof of Erasure image



The Auditor-Pro contains the following interfaces:

- 1. Ethernet Port
- 2. 4 USB (To connect with: intimus 20000, barcode scanner, thumbdrive, or optional mouse, and keyboard) 3. HDMI
- 4. 3.5 mm Image Capture Device interface
- 5. Power (Connects to standard wall outlet)

| SPECIFICATIONS | |
|---------------------------------|--|
| Storage capacity | 16 GB |
| Power supply | 90-240 VAC, 47-440 Hz |
| Power consumption | 15 W |
| Fuse | 250VAC H3. 15A |
| Media size / erase area size | 149 x 109 x 38 mm (5.8 x 4.3 x 1.5 in.) |
| Dimensions (HxDxW) | Control head: 167 x 243 x 63 mm (6.5 x 9.6 x 2.5 in.) Camera unit: 196 x 143 x 125 mm (7.7 x 5.6 x 4.9 in.) Degausser: 480 x 440 x 550 mm 18.8 x17.6 x 21.5 (in.) |
| Weight | Control head: 1,8 kg (4 lbs) Camera unit: 0,5 kg (1.2 lbs) Degausser: 66 kg (144 lbs) with case 104 kg (230 lbs) |
| Duty cycle | 45 s |
| Magnetic field | 20.000 Gauss / 2,0 Tesla |
| Warranty | One-year manufacturer's limited warranty |

WWW.INTIMUS.COM